



## WA-982-NBT

Double Needle Roller Feed With Backtracking & Thread Trimming  
Patented Sewing Machine WITH WHEEL FEED, NEEDLE  
FEED & DRIVEN

雙針滾輪送下直驅式羅拉自動切線  
及倒縫車 附輪型狗齒輪錢雙送式

TW專利權號碼：新型第 M296256  
CN專利權號碼：ZL 2005 2 0142755.1  
已申請多國專利仿冒必究

### 特點 / FEATURES

車頭一體成型,電腦加工,規格準確,內皮帶不易損壞。  
車頭穩重,操作不易振動。  
機頭可選配選針盒,更方便操作。  
直驅式馬達穩定性高,不易振動、省電。  
切線線頭比較短(1.2公分),減少人工剪線工時。  
倒縫針目準確對孔,不易損壞皮料,增加美觀。  
車縫跟倒縫雙滾輪帶動,故爬坡力強。(其他廠牌針車,倒縫無帶動)  
齒輪送及針送式輪錢,爬坡時仍能保持一定之縫目,不會大小針目。  
車縫海绵,薄類皮料,力保平滑均勻,不起皺,不曲形。  
新型針柱座(有申請專利),車縫時較穩定,減少斷針及斷線,車縫線路整齊美觀。  
增加手動倒縫,讓操作者更加方便使用。  
電磁閥設計,確實控制夾線器鬆線動作,使切線效果更臻完善。  
車頭特殊設計,車頭可安裝平行或傾斜兩用功能,無需另外加購斜臺。  
自動斷電設計,讓機修人員在維修保養時更安全。

### 用途及規格

用於：馬靴、運動鞋、工作鞋、休閒鞋、海绵鞋、嬰兒鞋、高級皮革鞋類縫製。  
最高縫速：每分鐘2,500針  
最大縫目：4.0mm  
針：DPX5

### USAGE

Ideal for boots sports shoes, work shoes, leisure shoes, foam rubber sole pads, babies shoes and high quality leather shoes.

The headstock of machine integrated with computer processing has exact specification and durable inner strap. It is steady to operate.

It's possible to choose the needle box, which provides easy operating.

Direct-drive motor has high stability and energy save.

To reduce the time of artificial trimming under short of 1.2 centimeters trim.

To form of accurately stitches by backtracking, with not easy to damage the leather and to increase the fair.

The sewing and backtracking with double rollers to work, and ensures hill climbing strength. (The other brands sewing machine without rolled of backtracking.)

The combined action of wheel and needle ensures constant stitches in both thick and thin sewing operation.

When spongy material is sewn, it will not transform; instead, it shall be sewn very smoothly and neatly.

The new needle clamp ( has the application patent), let sewn are stably. Several leather are sewn together & ensures less discrepancy in stitching.

Including backtracking lever in order to make user operating convenient.

Using solenoid valve design when trimmer to ensure to control thread tension of line action and make auto trimmer system perfect.

The headstock of machine by special designed, it's can be installed parallel of banked of both function, which is no need to purchase the innun.

Automatic power failure design obtains safety of servicemen in maintained.

### SPECIFICATIONS

Max. Sewing Speed: 2,500 S.P.M.

Max. Stitch Length: 4.0mm

Needle System: DPX5